

LW 300 E III Compact 420 bar



Compressors

Specifications

- » Electro motor
- » Painted steel frame and fan belt guard (RAL 6026)
- » Heavy duty compressor block components
- » Hour counter
- » Start/ Stop and emergency stop switch
- » Phase monitoring c/w shut down at wrong direction of rotation
- » Automatic stop at final pressure
- » Automatic Condensate Drain PRO (incl. Condensate-Stop-Valve, 0.8 l Prefilter and 10 Litre Condensate Tank)
- » HP-Outlet (c/w 1500mm high pressure hose)
- » Motor protection switch
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Improved lubrication system c/w oil filter
- » Low pressure oil pump and filter
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » 3 x concentric suction/pressure valves
- » Filling pressure 420 bar
- » Breathing air purification an accordance to EN 12021

Optionen

- » Auto start system
- » Oil pressure gauge
- » Intermediate pressure gauges
- » Oil pressure monitoring c/w auto shut down
- » Oil temperature display with auto shut down
- » Cylinder head temperature monitoring with auto shut down
- » Puracon filter monitoring
- » Remote Tab Control - RTC
- » Power cable and plug
- » Special voltages / frequencies on request



Technical Data

| LW 300 E III Compact 420 bar | |
|---|-------------------------------|
| Type: | Air cooled piston compressor |
| Capacity [litre/min] / [Nm³/h] / [cfm]: | 300 / 18.0 / 10.6 |
| Max. Pressure [bar]: | 420 |
| RPM [1/min]: | 840 |
| No of cylinders / No of stages: | 3 / 3 |
| Prime mover type: | E-Motor |
| Drive power [kW] with 50 Hz / 60 Hz: | 7.5 / 8.6 |
| Cooling air req. [m³/h] with 50 Hz / 60 Hz: | 2250 / 2580 |
| Lubrication type: | Oil pump + Splash oil |
| Oil capacity [litre]: | 2.7 |
| Oil pressure [bar]: | 1.5 (+/- 0.2) |
| Operating temperature [°C]: | +5°C to +40°C |
| Filter capacity [m³ at +20°C] ¹⁾ : | 900 (at +20°C / approx. 50 h) |
| Dimensions W x D x H [mm]: | 1650 x 775 x 920 |
| Weight [kg]: | 365 |
| Noise level (measured at 1 m) [dB(A)]: | 83 |

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0
Fax: +49 (0)62 56 - 8 58 80 -14
eMail: service@lw-compressors.com
Internet: www.lw-compressors.com

¹⁾ In accordance with EN 12021